


MICENAS LED Wall recessed



Description

Wall recessed for outdoor use.


For frontal lighting and downlighting. Includes flush-mounting box. Includes 2 cable outlets to facilitate chain mounting. Structure material: High purity aluminium. Structure finish: Urban grey. Diffuser material: Glass. Diffuser finish: Partly-sandblasted. UV protection. Warranty: 2 Years. Product net weight (Kg): 2.115 Product length (mm): 91 Product width or diameter (mm): 250 Product height (mm): 265 Class 1. Glow wire test: 850. IP: IP65. IK: IK10. LED. No. of lampholders or LEDs: 18. LED brand: OSRAM. Driver brand: EAGLERISE. Maximum power of light source: 20W. Colour temperature: Warm White - 3000K. Colour rendering index: 80. MacAdam Steps: 3. Hours of life: 50.000h L70B30. Photobiological risk: RG1. Real flux (lm): 504. Nominal flux (lm): 1862. Lm/Real W: 22. Voltage and frequency range: 100-240 VAC. Voltage: 3. Intensity: 40. Gear included: Yes, electronic. Multi-voltage gear included. Total power: 22.5W. Power factor: 0.96.

Finish

Urban grey
Partly-sandblasted

Material

High purity aluminium
Glass



TECHNICAL CHARACTERISTICS

Light source

Light source: LED OSRAM
Output (W): 20W
Total power consumption (W): 22.5W
Color temperature: Warm White - 3000K
CRI: 80
Real Lumen: 504
Nominal Lumen: 1862
Qty Leds: 18
Lm/Real W: 22
Life Time: 50.000h L70B30
Bin / Grup: 7S o 7T
MacAdam steps: 3
Photobiological risk: RG1

GEAR

Brand: EAGLERISE
Gear included: Yes, electronic
Voltage / Frequency:
100-240VAC/50-60Hz
Power Factor: 0.96

Luminaire

Double cable exit: Yes
Drainage: No
Uv Protection: Yes
Warranty: 2 Years

Logistics

Energy Efficiency: LED A++
EAN Code: 8435381454739
Net Weight (Kg): 2.115
Weight in Kg (packaged): 2.304
Packing: 270 x 260 x 115
Masterbox: 4

The photograph may not match the reference exactly. Please read the product description to identify the finish.

